Approved Wastewater Products in South Australia

Septic Tanks, Biological Filters, Holding Tanks & Pump Sumps

	Model	Capacity (L/EP)	Description	DHW Approval No. & expiry	AS/NZS 1546.1:2008 Certification No. & expiry
A&A Worm Farm Waste Systems Pty Ltd Hastings, VIC enquiries@wormfarm.com.au	PT 3200L G PT 3200L P	1,800L/d 12EP	Wet composting all-waste system with polypropylene shell, internal decomposition chamber with media utilising worms and invertebrates. Treated effluent must be disposed of via subsurface means (not including irrigation). Servicing recommended 12 months after commissioning, and every 2-5 years thereafter for life of system by a service agent accredited by A&A Worm Farm Waste Systems.	WWP-20220 4 June 2030	8717-4209-01 4 June 2030
	CT 3200L G CT 3200L P	3,200L/d 21.3EP	Wet composting all-waste system with concrete shell, internal decomposition chamber with media utilising worms and invertebrates. Treated effluent must be disposed of via subsurface means (not including irrigation). Servicing recommended 12 months after commissioning, and every 2-5 years thereafter for life of system by a service agent accredited by A&A Worm Farm Waste Systems.	WWP-20221 4 June 2030	
	CT 5000L G CT 5000L P	4,500L/d 30EP			
Access Septic Products Pty Ltd Lonsdale, SA admin@accessseptic.com.au	Access Septic 35	3,500L	Tank, fibreglass, horizontal orientation. Can be configured as a holding tank or a septic tank with baffle. Can be fitted with proprietary riser to a maximum depth of 2.5m to the top of the tank.	WWP-20213 17 November 2030	8413-4202-01 17 November 2030
	Access Septic 40	4,000L			
	Access Septic 50	5,000L			
	Access All in One 42	3,300L	Septic tank with baffle and 900L built-in pump sump, fibreglass, horizontal orientation. Can be fitted with proprietary riser to a maximum depth of 2.5m to the top of the tank.		
	Access All in One 50	4,100L			

Manufacturer	Model	Capacity (L/EP)	Description	DHW Approval No. & expiry	AS/NZS 1546.1:2008 Certification No. & expiry
Access Septic Products Pty Ltd Lonsdale, SA admin@accessseptic.com.au	Modifiable Volume Tanks DN1600	5,800 to 25,200L	Tank, glass-reinforced plastic, horizontal orientation. Can be configured as a holding tank/pump sump, septic tank, septic tank with pump chamber, Anaerobic Baffled Reactor (ABR) or ABR with pump chamber. ABR to be sized either in accordance with conventional septic tank sizing calculation, or using P2 x 3DF (whichever is greater). Can be fitted with proprietary riser to a maximum depth of 2.5m to the top of the tank. Approved tank volumes: 5,800L, 6,800L, 7,800L, 8,700L, 9,700L, 10,600L, 11,600L, 12,600L, 13,600L, 14,600L, 15,600L, 16,500L, 17,500L, 18,400L, 19,400L, 20,400L, 21,300L, 22,300L, 23,200L, 24,200L and 25,200L.	WWP-20211 17 November 2030	8413-4202-01 17 November 2030
	Modifiable Volume Tanks DN2400	16,900 to 82,000L	Tank, glass-reinforced plastic, horizontal orientation. Can be configured as a holding tank/pump sump, septic tank, septic tank with pump chamber, Anaerobic Baffled Reactor (ABR) or ABR with pump chamber. ABR to be sized either in accordance with conventional septic tank sizing calculation, or using P2 x 3DF (whichever is greater). Can be fitted with proprietary riser to a maximum depth of 4.5m to the top of the tank. Approved tank volumes: 16,900L, 21,100L, 25,500L, 29,800L, 34,100L, 38,400L, 42,700L, 47,000L, 51,400L, 55,700L, 60,000L, 64,800L, 69,100L, 73,400L, 77,700L and 82,000L.	WWP-20212 8 October 2030	8319-4202-01 8 October 2030
All Purpose Pumps Pty Ltd Hoppers Crossing, VIC sales@appumps.com.au	Ultima Vertical & Blu 0.6m diameter	180L 250L 320L 400L	Pump sump/holding tank, fibre-reinforced plastic fibreglass, vertical orientation. Variable capacity depending on inlet drill depth. Variable tank volumes depending on length of tank. Can be fitted with 250mm or 300mm riser.	WWP-20214 (Ultima Vertical) WWP-20215 (Ultima Blu) 2 July 2031	N/A

Manufacturer	Model	Capacity (L/EP)	Description	DHW Approval No. & expiry	AS/NZS 1546.1:2008 Certification No. & expiry
All Purpose Pumps Pty Ltd Hoppers Crossing, VIC sales@appumps.com.au	Ultima Vertical & Blu 1.0m diameter	500L	Pump sump/holding tank, fibre-reinforced plastic fibreglass, vertical orientation. Variable capacity depending on inlet drill depth. Variable tank volumes depending on length of tank. Can be fitted with 250mm or 300mm riser.	WWP-20214 (Ultima Vertical) WWP-20215 (Ultima Blu) 2 July 2031	N/A
		900L			
		1,300L			
		1,700L			
		2,080L			
		2,470L			
		2,860L			
	Ultima Vertical & Blu 1.2m diameter	1,100L			
		1,660L			
		2,230L			
		2,800L			
		3,360L			
		3,930L			
		4,480L			
		5,050L			
		5,620L			
		6,180L			
	Ultima Vertical & Blu 1.5m diameter	1,500L			
		2,400L			
		3,300L			
		4,200L			
		5,000L			
		5,900L			
		7,700L			
		9,590L			
	Ultima Vertical & Blu 1.8m diameter	2,800L			
		4,000L			
		5,300L			
		6,600L			
		7,900L			

Manufacturer	Model	Capacity (L/EP)	Description	DHW Approval No. & expiry	AS/NZS 1546.1:2008 Certification No. & expiry
All Purpose Pumps Pty Ltd Hoppers Crossing, VIC sales@appumps.com.au	Ultima Vertical & Blu 2.2m diameter	3,900L 5,800L 7,700L 9,600L 11,500L 15,300L 19,000L	Pump sump/holding tank, fibre-reinforced plastic fibreglass, vertical orientation. Variable capacity depending on inlet drill depth. Variable tank volumes depending on length of tank. Can be fitted with 250mm or 300mm riser.	WWP-20214 (Ultima Vertical) WWP-20215 (Ultima Blu) 2 July 2031	N/A
	Torpedo Horizontal 1.8m diameter	10,000L 15,000L	Pump sump/holding tank, fibre-reinforced plastic fibreglass, horizontal orientation. Variable tank volumes depending on length of tank. Can be fitted with adjustable priority riser with a maximum depth of 1.9m.	WWP-20216 2 July 2031	N/A
	Torpedo Horizontal 2.2m diameter	13,000L 20,000L 27,000L 35,000L 42,000L 45,000L 50,000L 55,000L 60,000L 65,000L 70,000L 75,000L			
	Ultima Mini Pump Station	230L 450L	Ultima mini packaged pump station, polyethylene, horizontal orientation. Aboveground Installation.	WWP-20217 2 July 2031	N/A

Manufacturer	Model	Capacity (L/EP)	Description	DHW Approval No. & expiry	AS/NZS 1546.1:2008 Certification No. & expiry
Arris Pty Ltd Urrbrae, SA info@arris.com.au	Rhizopod®	N/A	Recirculating effluent evapotranspiration system consisting of a concrete or plastic vessel with plants. Used in conjunction with an on-site wastewater system and a balance tank sized to hold a minimum 4 days hydraulic flow. Concrete vessels can be installed above ground or buried to ground level, plastic vessels must be buried to ground level. Setbacks to buildings to be determined by a structural engineer.	WWP-20206 13 October 2030	N/A
Aquatec Fluid Systems Pty Ltd Shepparton, VIC info@aquatecenviro.com	Simplex	600L	Packaged pressure sewer pump unit, polyethylene, vertical orientation.	WWP-20097/A 28 September 2026	BMP 657673 28 September 2026
	Enviroplex	900L			
	Simplex	1,100L			
	Duplex	1,500L			
	Enduraplex	950L	Packaged pump sump, polyethylene, vertical orientation.	WWP-20164 12 December 2027	SMK41326 12 December 2027
BioCycle Sheidow Park, SA sales@biocycle.com.au	Septic Tank	3,000L	Septic tank with baffle, concrete, horizontal orientation.	WWP-20166 9 August 2029	SMKB20210 9 August 2029
		3,250L			
		4,250L			
		8,000L	Septic tank with baffle, concrete, vertical orientation.		
Bio-Logical Waste Systems Pty Ltd T/A Wormsmart Wauchope, NSW info@wormsmart.com.au	WormSmart AWSP1800PF	10EP	Wet composting all-waste system with decomposition chamber utilising worms and invertebrates. Treated effluent must be disposed of via subsurface means (not including dripper irrigation). System must be serviced every 6 months by service agent accredited by WormSmart.	WWP-20120 25 August 2026	339 25 August 2026
	Wormlet Model WLET550PE	550L/d	Wet composting all-waste system with decomposition chamber utilising worms and invertebrates. Treated effluent must be disposed of via subsurface means (not including dripper irrigation). System must be serviced every 18-24 months by a service agent accredited by WormSmart.	WWP-20201 25 August 2026	SMK 1950 25 August 2026

Manufacturer	Model	Capacity (L/EP)	Description	DHW Approval No. & expiry	AS/NZS 1546.1:2008 Certification No. & expiry
Coerco Pty Ltd Dalwallinu, WA info@coerco.com.au	VUT600	600L	Pump sump, polyethylene, vertical orientation.	WWP-20170 2 November 2029	SMK40330 2 November 2029
	VUT900	900L			
	VUT1200	1,200L			
	SEP-1450	1,450L	Tank, polyethylene, vertical orientation. Can be configured as a septic tank with baffle or holding tank.	WWP-20171 2 November 2029	
	SEP-2200	2,200L			
	SEP-3200 NEP-3200	3,200L			
	SEP-4000 NEP-4000	4,000L			
	SEP-7000	7,000L	Tank, polyethylene, horizontal orientation. Can be configured as a septic tank with baffle or holding tank.	WWP-20172 2 November 2029	
	SEP-11000	11,000L			
	SEP-15000	15,000L			
	SEP-19000	19,000L			
	SEP-23000	23,000L			
	SEP-27000	27,000L			
	SEP-31000	31,000L			
Department for Environment and Water (DEW) Adelaide, SA	National Parks and Wildlife Service (NPWS) Waterless Holding Tank Toilet System	850L	Waterless public toilet system composed of a toilet pedestal, subsurface polyethylene holding tank, and vent with wind-driven turbine ventilator, designed for use in national parks. Toilet block building will require footings to be engineered to cater for holding tank located within building foundation footprint. Not designed to accept plumbing fixture waste.	WWP-20086/2 23 September 2028	SMKB20032 23 September 2028 SMK40227 20 January 2029
		1,050L			
		1,460L			
		3,200L			
Enviro One Services Cleveland, QLD	E/One Grinder Pump Station Model 2010iW	600/650L	Packaged grinder pump station, polyethylene, vertical orientation. Can be fitted with a proprietary “Model CM9125” extension collar.	WWP-20025/A 11 May 2028	SMKB20051 11 May 2028
	E/One Grinder Pump Station Model 2013iW	850/900L	Packaged grinder pump station, polyethylene, vertical orientation.		

Manufacturer	Model	Capacity (L/EP)	Description	DHW Approval No. & expiry	AS/NZS 1546.1:2008 Certification No. & expiry
Enviro One Services Cleveland, QLD	E/One Grinder Pump Station Model 2014iW	1,290/ 1,500L	Packaged grinder pump station, polyethylene, vertical orientation. Can be fitted with a proprietary "Model CM9125" extension collar.	WWP-20025/A 11 May 2028	SMKB20051 11 May 2028
Everhard Industries Geebung, QLD info@everhard.com.au	Septic Tank/Holding Tank	3,000L	Tank, Polypropylene, vertical orientation. Can be configured as a septic tank with baffle or holding tank. Can be fitted with a proprietary riser.	WWP-20142 2 June 2028	SMK01950 2 June 2028
		4,000L	Tank, Polypropylene, vertical orientation. Can be configured as a septic tank with baffle or holding tank.		
	Pump Well	250L or 450L	Pump sump, polyethylene, spherical orientation. Can be fitted with a proprietary riser.		
Fluid Environmental Pty Ltd Urrbrae, SA info@fluidenviro.com.au	ABSORBS Zero Discharge recirculating effluent evapotranspiration unit (concrete vessel)	N/A	Recirculating effluent evapotranspiration system consisting of a concrete vessel planted with vegetation. Used in conjunction with an on-site wastewater system and a balance tank sized to hold a minimum 4 days hydraulic flow. Concrete vessels can be installed above ground or buried to ground level. Setbacks to buildings to be determined by a structural engineer.	WWP-20207 11 May 2031	N/A
	ABSORBS Zero Discharge recirculating effluent evapotranspiration unit (in-ground lined trench)	N/A	Recirculating effluent evapotranspiration system consisting of a HDPE lined inground trench, planted with vegetation. Used in conjunction with an on-site wastewater system and a balance tank sized to hold a minimum 4 days hydraulic flow. Wastewater distribution is achieved either through pressure dosed arch tunnel or through subsurface drippers when secondary treated effluent is used. Setbacks to buildings to be determined by a structural engineer.		

Manufacturer	Model	Capacity (L/EP)	Description	DHW Approval No. & expiry	AS/NZS 1546.1:2008 Certification No. & expiry
Global Water Tonsley, SA sales@globalwatergroup.com.au	DAP02A	250L	DrainAce Pressure Sewer Simplex Packaged Pump Station, polyethylene, vertical orientation.	WWP-20191 20 January 2029	TBD
	DAP03A	320L			
	DAP04	450L			
	DAP06A	590L			
	DAP09	950L			
	DAP10A	1,050L			
	DAP10P	1,050L			
	DAP15	1,460L			
	DAP19	1,880L			
	DAP22	2,180L			
	DAP28	2,780L			
	DAP31	3,150L			
	DAP32	3,200L			
	DAP40	4,000L			
	DAP41	4,100L			
	DAP45	4,500L			
	DAP52	5,200L			
	DAP60	6,000L			
	DAP61	6,100L			
	DAP69	6,900L			
	DAP81	8,100L			
	DAP105	10,500L			
	DAC54	5,400L	DrainAce packaged pump station, concrete, vertical orientation. Can be fitted with an optional cover slab for class B and D vehicle trafficability.	WWP-20203 13 October 2030	SMK1659 13 October 2030
	DAC98	9,800L			
	DAC136	13,640L			
	DAC226	22,600L			
	EnviroLift PPM	4,500L to 25,300L	Packaged pump sump, concrete, vertical orientation. Standard unit can be installed with optional increments to expand capacity of the sump to a maximum specified depth. Variable capacity depending on inlet depth.	WWP-20218 4 June 2031	N/A
	EnviroLift PPL	7,000L to 59,000L			

Manufacturer	Model	Capacity (L/EP)	Description	DHW Approval No. & expiry	AS/NZS 1546.1:2008 Certification No. & expiry
Global Water Tonsley, SA sales@globalwatergroup.com.au	EnviroLift PPG	14,000L to 118,000L	Packaged pump sump, concrete, vertical orientation. Standard unit can be installed with optional increments to expand capacity of the sump to a maximum specified depth. Variable capacity depending on inlet depth.	WWP-20218 4 June 2031	N/A
	EnviroLift PPXM	4,500L to 24,500L			
	EnviroLift PPXL	4,100L to 53,500L			
	EnviroLift PPXG	6,600L to 101,400L			
	EnviroLift Volym	16,800L to 172,700L			
Global Water Tonsley, SA *Distributed by* **Eco Building Supplies** Seaview Downs, SA admin@ecobuildingsupplies.com.au **Pump Stations Australia** Seacliff Park, SA office@pumpstationsaustralia.com.au	Pump stations	1,050L 850mm diameter	Pump stations, polyethylene, vertical orientation.	WWP-20168/1 and WWP-20169/1 20 January 2029	TBD
		1,050L 1,000mm diameter			
		1,460L			
		1,880L			
		3,150L			
		3,200L			
		4,100L			
		6,100L			
		8,500L			
Global Rotomoulding Helidon Spa, QLD info@globalwater.com.au	GR-SP2500	2,500L	Septic tank (with or without baffle), polyethylene, spherical orientation.	WWP-20175 20 April 2030	SMK40297 20 April 2030
	GR-SP3000	3,000L			
	GR-SP4500	4,500L	Septic tank (with or without baffle), polyethylene, spherical orientation. Can be installed with a 300mm riser.		
	GR-SP5000	5,000L			
	GR-SP6000	6,000L			

Manufacturer	Model	Capacity (L/EP)	Description	DHW Approval No. & expiry	AS/NZS 1546.1:2008 Certification No. & expiry
Global Rotomoulding Helidon Spa, QLD info@globalwater.com.au	GR-2RBDT570	570L	Holding tank/pump sump, polyethylene, horizontal orientation. Can be used as a dosing chamber in the Surge-Flow100 reed bed container (Reed-ePod).	WWP-20175 20 April 2030	SMK40297 20 April 2030
	GR-POC550	550L	Holding tank/pump sump, polyethylene, vertical orientation.		
	GR-POC1000	1,000L			
Gough Plastics Bohle, QLD sales@gough.com.au	Hybrid Toilet System	6EP	Public toilet primary-treatment system consisting of a proprietary low/no flush toilet pedestal, waste collection/treatment tank(s), vent with wind-driven or powered turbine, and effluent disposal system in accordance with the Code. Can accept hand basin waste.	WWP-20141 23 April 2028	SMKB21477 23 April 2028
		10EP			
		25EP			
		50EP			
		75EP			
		100EP			
		150EP			
GRAF Australia Pty Ltd Henderson, WA info@grafaustralia.com.au	Carat	2,700L	Septic tank (with or without baffle), pump sump or holding tank, polypropylene, horizontal orientation. Can be fitted with proprietary risers. Can be made trafficable for class B and D vehicle loads.	WWP-20159 26 April 2029	5669-3054-02 26 April 2029
		3,750L			
		4,800L			
		6,500L			
	Carat XL	8,500L	Septic tank (without baffle), pump sump or holding tank, polyethylene, horizontal orientation. Can be fitted with proprietary risers. Can be made trafficable for class B and D vehicle loads.	WWP-20155 26 April 2029	
		10,000L			
	Carat XXL	16,000L	Septic tank (without baffle), holding tank or pump sump, polyethylene, horizontal orientation. Can be fitted with proprietary risers. Can be made trafficable for class B and D vehicle loads.	WWP-20167/1 26 April 2029	
		22,000L			
		26,000L			
		28,000L			
		32,000L			
		36,000L			
		38,000L			
		42,000L			
		46,000L			
		48,000L			
		52,000L			

Manufacturer	Model	Capacity (L/EP)	Description	DHW Approval No. & expiry	AS/NZS 1546.1:2008 Certification No. & expiry
GRAF Australia Pty Ltd Henderson, WA info@grafaustralia.com.au	Sapphire	600L 900L 1,200L 1,500L	Pump sump/holding tank, polyethylene, vertical orientation. Can be fitted with proprietary risers. Can be made trafficable for class B and D vehicle loads.	WWP-20160 26 April 2029	5669-3054-02 26 April 2029
	SuperCompact	2,000L 3,000L 4,000L 5,000L 8,000L 10,000L	Pump sump/holding tank, polyethylene, horizontal orientation. Can be fitted with proprietary risers. Can be made trafficable for class B and D vehicle loads.	WWP-20155 26 April 2029	
	Platin/ Garantia Li-Lo	1,500L 3,000L 5,000L 7,500L 10,000L 15,000L 20,000L 25,000L	Pump sump/holding tank, polyethylene, horizontal orientation. Can be fitted with proprietary risers. Can be made trafficable for class B and D vehicle loads.	WWP-20087/2 28 October 2029	5669-3054-04 28 October 2029
	SuperStrong/ Garantia SuperStrong	600L 900L 1,200L 1,500L	Rotationally moulded polyethylene tank, vertical orientation. Can be fitted with proprietary risers (600L, 900L and 1200L models only). Can be made trafficable for class B and D vehicle loads.	WWP-20204 28 October 2029	
Hengshui Aoliancle Trading Heibi, China *Distributed by* Ecoflo Wastewater Management Virginia, QLD info@ecoflo.com.au	Nature Clean SMC Horizontal Septic Tank	2,500L (working capacity 2,300L)	Dual baffle 2,500L glass fibre reinforced plastic horizontal septic tank.	WWP-20104 3 October 2026	669 3 October 2026

Manufacturer	Model	Capacity (L/EP)	Description	DHW Approval No. & expiry	AS/NZS 1546.1:2008 Certification No. & expiry
Plastek Industries Pty Ltd Delacombe, VIC info@plastekind.com.au	Septic Tank	1,800L	Septic tank with baffle, concrete, horizontal orientation.	WWP-20119 9 November 2026	SMK41214 9 November 2026
		3,300L			
		5,000L			
	Pump Well/ Holding Well	2,200L	Holding tank/pump sump, concrete, vertical orientation.		
		3,600L			
		5,500L			
Polymaster Swan Hill, VIC sales@polymaster.com.au	Pump Well	700L	Pump sump, polyethylene, vertical orientation. Can be fitted with a proprietary riser	WWP-20153/1 28 September 2026	BMP 657673 28 September 2026
		1,000L			
		1,300L			
	ST3100	3,100L	Septic tank without baffle, polyethylene, horizontal orientation. Can be fitted with a proprietary riser.	WWP-20139/2 28 September 2026	
	ST4550	4,550L			
	CW3300	3,300L	Holding tank, polyethylene, horizontal orientation. Can be fitted with a proprietary riser.		
	CW5000	5,000L			
Quickmix Concrete Mount Gambier, SA admin@quickmix.com.au	Septic Tank	3,400L	Septic tank, concrete, horizontal orientation.	WWP-20154 18 December 2028	SMK1661 18 December 2028
	Septic Tank	6,000L	Septic tank, concrete, vertical orientation.		
	Collection Well	6,000L	Holding tank, concrete, horizontal orientation.		
RELN Pty Ltd Ingleburn, NSW sales@reln.com.au	450L/600L Pump Well	450L or 600L	Pump sump, polyethylene, vertical orientation. Capacity 450L or 600L depending on inlet drill location.	WWP-20183 19 July 2028	AMI 1651 19 July 2028
	1200L/1000L/ 900L Pump Well	900L or 1,000L	Pump sump, polyethylene, vertical orientation. 1,200L nominal capacity. Usable capacity of 900L or 1,000L depending on inlet drill location.		
	3200L Septic Tank/Holding Tank	3,200L	Tank, polypropylene, vertical orientation. Can be configured as a holding tank or a septic tank with baffle. Can be fitted with a proprietary riser.		
	4000L Septic Tank/Holding Tank	4,000L	Tank, polypropylene, vertical orientation. Can be configured as a holding tank or a septic tank with baffle.		

Manufacturer	Model	Capacity (L/EP)	Description	DHW Approval No. & expiry	AS/NZS 1546.1:2008 Certification No. & expiry
Ri-Industries Angle Park, SA sales@ri-industries.com.au	Pump Chamber	1,100L	Pump sump, plastic fibre-reinforced concrete, vertical orientation. Can be fitted with 450mm or 900mm riser.	WWP-20202 13 October 2030	SMK1659 13 October 2030
	Septic Tank	1,620L	Septic tank with baffle, concrete, horizontal orientation. Can be fitted with a proprietary “Type 33” riser.	WWP-20182 13 October 2030	SMK1659 13 October 2030
		3,000L 50mm wall			
		3,000L 60mm wall			
		3,250L			
	Septic Tank/ Holding Tank	4,300L	Septic tank with baffle or holding tank, concrete, horizontal orientation. Can be fitted with proprietary “Type 33” riser.		
		5,000L			
	Septic Tank/ Holding Tank	5,000L	Tank, concrete, vertical orientation. Can be configured as a holding tank or septic tank with baffle. Can be fitted with proprietary risers. Come in trafficable and non-trafficable versions. Can be made trafficable for Class B and D vehicle loads.	WWP-20190 13 October 2030	
		8,000L			
		12,000L			
		20,000L			
	Ri-Scape 3300	3,300L	Combined septic tank with baffle and internal 900L pump chamber, concrete, horizontal orientation. Can be fitted with proprietary riser and cover slab with lockable poly resin access lid.	WWP-20177 13 October 2030	
	Ri-Scape 4000	4,000L			
	RI-ABR6470	6,470L	Septic tank, concrete, vertical. Contains six chambers. Tank body can have increments fitted from 300-900mm. Can be installed with 300mm, 450mm, and 600mm risers.	WWP-20189 13 October 2030	

Manufacturer	Model	Capacity (L/EP)	Description	DHW Approval No. & expiry	AS/NZS 1546.1:2008 Certification No. & expiry
Rotoplas Unanderra, NSW sales@rotoplas.com.au	VUT100	100L	Pump sump/holding tank, polyethylene, vertical orientation.	WWP-20219 4 November 2030	BMP 728571 4 November 2030
	VUT250	250L	Pump sump/holding tank, polyethylene, vertical orientation. Can be fitted with proprietary 150mm or 300mm risers. Can be made trafficable for Class B and D vehicle loads.		
	VUT350	350L			
	VUT700	700L			
	VUT1200	1,200L			
	VUT1600	1,600L			
	VUT2000	2,000L			
	VUT3000	3,000L	Pump sump/holding tank, polyethylene, vertical orientation. Can be made trafficable for Class B and D vehicle loads.		
	VUT5000	5,000L			
Suncoast Waste Water Management Kunda Park, QLD info@ozzikleen.com	PT 300	300L	Pump sump/holding tank, polyethylene, vertical orientation.	WWP-20146/1 23 September 2028	SMKB20032 23 September 2028
	PT 350	350L			
	PT 500	663L			
	PT 850	850L			
	PT 1000 (flat bottom)	1,208L			
	PT 1000 (hopper bottom)	1,225L			
	PS 1000	1,225L			
	PT 1500 (flat bottom)	1,735L			
	PT 1500 (hopper bottom)	1,640L	Pump sump/holding tank, polyethylene, vertical orientation.		
	PS 1500	1,640L			
	PT 4000	4,150L	Pump sump/holding tank, polyethylene, vertical orientation. Comes in single and twin turret versions.		
	PT 5300 (flat bottom)	5,350L	Pump sump/holding tank, polyethylene, vertical orientation.		

Manufacturer	Model	Capacity (L/EP)	Description	DHW Approval No. & expiry	AS/NZS 1546.1:2008 Certification No. & expiry
Suncoast Waste Water Management Kunda Park, QLD info@ozzikleen.com	PT 5300 (hopper bottom)	5,250L	Pump sump/holding tank, polyethylene, vertical orientation.	WWP-20146/1 23 September 2028	SMKB20032 23 September 2028
	RW 5300	5,300L			
	ST10	4,500L	Tank without baffle, polyethylene, vertical orientation. Can be configured as a septic tank without baffle, a holding tank or a pump sump.		
	ST10A	4,500L	Septic tank with baffle, polyethylene, vertical orientation.		
Sustainable Space Clare, SA essentialfx@gmail.com	Reed ePod Mk2	N/A	Biological outlet filter incorporating reed bed contained in a Global Rotomoulding polyethylene open-top trough. Installed after septic tank with outlet filter. Multiple units may be installed in series. Effluent disposal via primary-treated effluent disposal methods in Code or AS/NZS 1547.	WWP-20136 27 April 2028	N/A
Taylex Australia Pty Ltd Ormeau, QLD info@taylex.com.au	Maxi Tank	4,750L	Septic tank, concrete, vertical orientation. Contains five chambers and clarification TFS filter. Can be fitted with internal pump in final chamber (453L). Can be installed with 600mm, 800mm and 1,000mm risers.	WWP-20185 11 July 2030	7295-3039-01 11 July 2030
	Septic Tank	4,000L	Tank, concrete, vertical orientation. Can be configured as a septic tank with or without baffle, or holding tank, or pump chamber. Can be installed with 600mm, 800mm and 1,000mm risers. The 5,000L and 10,000L septic tanks can be made trafficable for class B and D vehicle loads.	WWP-20184 11 July 2030	
	Septic Tank	5,000L			
	Septic Tank	10,000L			
	22,500L, T44 Septic Tank	18,960L	Tank, concrete, vertical orientation. Can be configured as a septic tank without baffle and with inlet and outlet sweep tees, or holding tank, or pump chamber. Optional outlet filter. Can be fitted with a 150mm riser. Can be made trafficable for Class B and D vehicle loads.	WWP-20186 19 August 2030	7290-3039-01 19 August 2030

Manufacturer	Model	Capacity (L/EP)	Description	DHW Approval No. & expiry	AS/NZS 1546.1:2008 Certification No. & expiry
Taylex Australia Pty Ltd Ormeau, QLD info@taylex.com.au	10,000L Pump Station / Balance Tank / Invert Tank	6,000L 6,460L 7,250L 7,680L 8,500L 8,900L	Tank, concrete, vertical orientation. Can be configured as a holding tank or a pump sump. Variable capacity depending on inlet depth. Can be fitted with 600mm, 800mm and 1,000mm risers. Can be made trafficable for Class B and D vehicle loads.	WWP-20186 19 August 2030	7290-3039-01 19 August 2030

Note:

Where trafficability is not specified for products on this list, a bespoke trafficable lid designed by a wastewater water engineer may be used. Alternatively, a proprietary trafficable lid may also be used if certified by a wastewater engineer. Trafficable lids must be designed and used so that the tank is not subject to any trafficable loads, and that these loads are diverted around the tank.

More information:
Wastewater Management
Health Protection and Regulation
SA Health
Citi Centre Building
11 Hindmarsh Square
Adelaide SA 5000

PO Box 6
Rundle Mall SA 5000

Tel: (08) 8226 7100
Fax: (08) 8226 7102
Email healthwastewatermanagement@sa.gov.au

http://www.sahealth.sa.gov.au/wastewater

ABN 97 643 356 590

© Department for Health and Wellbeing, Government of South Australia.
All rights reserved.

Last revised 11 September 2026

Government of South Australia
SA Health